

tesa® 4611 Tunnel tape

tesa® 4611 is a strong acrylic coated cloth tape with a neutralized part of the adhesive side in the middle. It is based on a 120 mesh woven rayon fabric backing and a natural rubber adhesive. tesa® 4611 is an excellent solution for "Arts & Entertainment" applications.

Features:

- high adhesion even on rough surfaces
- excellent tensile strength
- conformable
- easy to remove without residues
- no unpleasant smell
- very matt surface
- can be removed without leaving any residues from almost any surface
- available in black

The advantage of this tape vs. other tape solutions is the possibility to pull cables, cords or wires, even after fixing them on the surface.

Main Application

- For cable fixing applications on stages, in the backstage areas in theaters, opera, concert halls, conventions and conferences.

Technical Data

▪ Backing material	acrylic-coated cloth	▪ Temperature resistance (30 min)	140 °C
▪ Type of adhesive	natural rubber	▪ Mesh	120 count per square inch
▪ Adhesion to steel	3.8 N/cm	▪ Surface finish	matt

Properties

▪ Hand tearability	●●●●	▪ Easy to write on	yes
▪ Straight tear edges	●●●●	▪ Abrasion resistance	●●●●
▪ Easy to remove	yes	▪ Water resistance	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

Recommendation: please conduct a test on the application surface before using the product.

For latest information on this product please visit <http://l.tesa.com/?ip=04611>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.