

# PRODUCT DATA SHEET



## RED HARD WOOD FLOOR PROTECTION FILM – IE201

### DESCRIPTION

Temporary protection of matt surfaces of hard wood, painted metals and plastic laminates, PVC profiles / laminates.

*NB: Do not use on PVDF, Plastisol, Polyurethane paints. Not suitable for protection against corrosion, humidity or chemical solvents.*

PROPERTIES	UNIT MEASURE	DETAILS
Film Type		Polyethylene (LDPE)
Average thickness (A.F.E.R.A. 4006)	Micron	45
Colour		Red
Adhesive type		Acrylic
Adhesion to steel (A.F.E.R.A. 4001)	cN/cm	90
Longitudinal tensile strength (A.F.E.R.A. 4004)	daN/cm	>1
Transversal tensile strength (A.F.E.R.A. 4004)	daN/cm	>0.7
Longitudinal max. elongation (A.F.E.R.A. 4005)	%	>200
Transversal max. elongation (A.F.E.R.A. 4005)	%	>470

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.

Reliable Source Ltd – 1 High Street – Chislehurst – Kent – BR7 5AB  
T: 020 8295 5440 F: 020 8295 5441  
E: sales@reliablesource.co.uk W: www.reliablesource.co.uk