

PRODUCT DATA SHEET



SELF ADHESIVE HOOK AND LOOP – RSX10 & RSX11

DESCRIPTION

A high tack hot-melt rubber based adhesive system, coated to the back of hook & loop tape offering instant bond to most surfaces.

TECHNICAL DATA

Adhesive colour:	Light Yellow
Performance:	A strong instant bond
Typical Application:	Immediate adhesion to a variety of surfaces including paper, wood, polythene, metal, glass, plastic etc (excluding plasticised PVC).
Material - Base (backing):	80% Nylon/20%PE
Material - Hooks & Loops:	80% Nylon/20%PE
Weight:	360g/m ²
Peel strength:	3.5N/cm
Shear strength:	18N/cm ²
Hooks per square inch:	300
Loops per square inch:	330
Application Guide:	To be avoided on surfaces of humidity, dust, oil etc. Application temperature from +5 to +40 degree C.

Customer Attention: The above points are suggestions and are not to be considered guarantees. All tapes should be tested in working conditions before long term use.

Not recommended for direct exposure to sunlight & U.V.

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.

Reliable Source Ltd – 1 High Street – Chislehurst – Kent – BR7 5AB
T: 020 8295 5440 F: 020 8295 5441
E: sales@reliablesource.co.uk W: www.reliablesource.co.uk