

PRODUCT DATA SHEET



PREMIUM ULTRA BOND DOUBLE SIDED FILMIC – RS314

DESCRIPTION

Our Premium Ultra Bond Double Sided Filmic Tape uses a 12 micron PET film as carrier, coated with a mould resistant cold weather solvent acrylic adhesive on both sides, and protected with white colour double-sided PE coated silicone release paper. Suitable for general bonding, bag sealing, photos sticking, envelop sealing, shopping bag making, fabric / leather laminating, paper and film flying splicing, fabric positioning during computer embroidering, carpet fixing, foam laminating and die-cutting etc.

TECHNICAL DATA

Adhesive	Solvent Acrylic
Total Thickness	170 Micron
Adhesion to Steel	25 N/25mm
Tack Rolling Ball	10cm
Adhesion to Liner	0.5 N/25mm
Service Temperature	-30 ~ +120°C
Applying Temperature	+10 ~ 40°C
Shelf Life	12 Months

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.

Reliable Source Ltd – 1 High Street – Chislehurst – Kent – BR7 5AB
T: 020 8295 5440 F: 020 8295 5441
E: sales@reliablesource.co.uk W: www.reliablesource.co.uk