

# PRODUCT DATA SHEET



## D/S FINGERLIFT TISSUE TAPE – RS430

### DESCRIPTION

A double sided tissue tape with fingerlift edge liner.

### TECHNICAL DATA

<b>Adhesive</b>	Hotmelt Rubber
<b>Thickness (Adhesive + Carrier)</b>	0.080mm
<b>Release Liner Thickness</b>	0.065mm
<b>180° Peel Adhesion (Open Side)</b>	900 N/m
<b>180° Peel Adhesion (Closed Side)</b>	900 N/m
<b>Polyester Loop Tack (Open Side)</b>	850 N/m
<b>Polyester Loop Tack (Closed Side)</b>	850 N/m
<b>Liner Release</b>	10 N/m
<b>Tensile Strength</b>	1200 N/m
<b>Elongation at Break</b>	10%
<b>Service Temperature</b>	-10 to +60°C
<b>Application Temperature</b>	+5 to +25°C

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.

Reliable Source Ltd – 1 High Street – Chislehurst – Kent – BR7 5AB  
T: 020 8295 5440 F: 020 8295 5441  
E: [sales@reliablesource.co.uk](mailto:sales@reliablesource.co.uk) W: [www.reliablesource.co.uk](http://www.reliablesource.co.uk)