

# PRODUCT DATA SHEET



## BLACK PALLET – RS695

### DESCRIPTION

A polyethylene stretch film for pallet wrapping either by hand or on mechanised pallet wrap machines.

### NOMINAL DIMENSIONAL CHARACTERISTICS

WIDTH To order + / - 5mm

LENGTH (m) To order At least stated length

GAUGE (mu) To order + / - 10%(Gravimetric Average) DENSITY (gm/cc) 0 - 92 +/- 0.5% TYPICAL FILM PROPERTIES MICRONS	14mu	17mu	20mu	25mu
BREAK ELONGATION (%)	380	410	450	470
DART IMPACT (grams)	50	60	75	85
PRE-STRETCH (%)	0-80	0-100	0-130	0-160
TENSILE STRENGTH (Mpa)	37	37	37	37
YIELD (M <sup>2</sup> /kg)	78.1	64.3	54.6	47.5

Every endeavour has been made to ensure that the information given herein is true and reliable but is given only for guidance for our customers without any guarantee.

Users are advised to confirm the suitability of our recommendation by their own tests.

This film is not for use in direct contact with food

All Blown Film is made of LLDPE (Linear Low Density Polyethylene). Our film does not contain any trace of silicon.

All Film is 100% recyclable but not bio-degradable.

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.

Reliable Source Ltd – 1 High Street – Chislehurst – Kent – BR7 5AB

T: 020 8295 5440 F: 020 8295 5441

E: sales@reliablesource.co.uk W: www.reliablesource.co.uk