

PRODUCT DATA SHEET



ANTI-CORROSION TAPE – RSX15

COMPOSITION

Durable synthetic fibre fabric impregnated and coated with a petrolatum compound.

USES

Conformable, cold-applied petrolatum tape used for the corrosion protection of buried or exposed pipes, valves, and fittings.

- Resistant to water, water vapour and gases
- Resistant to mineral acids, alkali and salts
- Non-hardening, non-cracking
- Conformable over a wide temperature range

Service temperature: -20°C to +55°C

Application temperature: -5°C to +45°C

AVAILABILITY

The tape is available in 10 metre rolls in widths from 50mm to 300mm.

STORAGE CONDITIONS

Store in a cool and dry place in original packaging.

TYPICAL PROPERTIES

Breaking Strength	200 N/50mm minimum
Elongation at Break	10%
Breakdown Voltage	16kV minimum per double layer
Total Thickness	1.15 mm
Weight	1.44 kg/m ²

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.

Reliable Source Ltd – 1 High Street – Chislehurst – Kent – BR7 5AB

T: 020 8295 5440 F: 020 8295 5441

E: sales@reliablesource.co.uk W: www.reliablesource.co.uk