

PRODUCT DATA SHEET



NEC APPROVED D/S TAPE – RS360

DESCRIPTION

These tapes are of Printed, 60 micron Low Density Polyethylene Film carrier, coated on the Open Side with a Low-Tack Peelable adhesive and on the closed side with High-Tack Permanent adhesive, with an 80gsm White Glassine Release Liner, and are sideways-tearable.

TYPICAL APPLICATION

Ideally suited for temporary carpet-laying, as at exhibitions.

APPLICATION

The Open Side (i.e. That which is exposed as the tape is wound off the roll) is applied to the Exhibition Floor, which must be clean, and the Release Liner removed to expose the Permanent adhesive on to which the underside of the Exhibition Carpet is firmly placed. The peelable side to the floor can therefore be removed without leaving residue.

STORAGE CONDITIONS

Store in a cool and dry place in original packaging.

TECHNICAL DETAILS

TYPICAL VALUES

Adhesive colour	Clear
Adhesive type	Pure acrylic
Tape thickness (Carrier & Adh)	1.108mm
Carrier thickness	0.060
Peel Adhesive (steel) 24hrs	120/920N/M
Loop Tack	140/640N/M
Shear static (Hrs @ 1KG)	1/120
Temp °C Min Application	+5°C/-5°C
Service range	-20 to +120°C
Shelf life	12 months PSTMA Conditions

Continued...

Reliable Source Ltd – 1 High Street – Chislehurst – Kent – BR7 5AB
T: 020 8295 5440 F: 020 8295 5441
E: sales@reliablesource.co.uk W: www.reliablesource.co.uk

WARRANTIES

These figures are average values and should not be regarded as maximum or minimum values for specification purposes.

The Purchaser shall be responsible for determining the suitability of this product for his purposes.

We shall not be liable for consequential damage incurred in the use of this material.

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.

Reliable Source Ltd – 1 High Street – Chislehurst – Kent – BR7 5AB

T: 020 8295 5440 F: 020 8295 5441

E: sales@reliablesource.co.uk W: www.reliablesource.co.uk