

PRODUCT DATA SHEET



PINK HEAVY DUTY PLASTERERS SCRIM – RS444PK

DESCRIPTION

This fibreglass re-enforced plasterer's tape is backed with a pressure sensitive adhesive. Quick and easy to apply, with a high tack adhesive and an open mesh that won't blister or bubble. Used for jointing dry walling, repairing large cracks in plaster and in ceiling work.

APPLICATION

Ensure all surfaces are clean, dry and free from oil, grease and dust. Place tape into position and apply directly to joint or crack, pressing firmly to ensure good adhesion. For crack and hole repairs, the tape must be extended at least 25mm from the edge of the area to be repaired, butting (never overlapping) the tape.

TECHNICAL DETAILS

	STANDARD	AVERAGE VALUE
Tensile Strength (N/50mm)		
Warp	500	622
Weft	500	578
Warp & Weft Density (Ends per inch)		
Warp	9±1	9
Weft	9±1	9
Gum Containing (%)	30±2	30
Area Weight (g/m)	65±5	65

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.

Reliable Source Ltd – 1 High Street – Chislehurst – Kent – BR7 5AB
T: 020 8295 5440 F: 020 8295 5441
E: sales@reliablesource.co.uk W: www.reliablesource.co.uk